# iiyama TF3239AS-B1AG signage display Płaski panel Digital Signage 80 cm (31.5") LED 500 cd/m² 2.4K Ultra HD Czarny Ekran dotykowy Procesor wbudowany Android 24/7







**Marka :** iiyama

**Kod produktu:** TF3239AS-B1AG

**Nazwa produktu :** TF3239AS-B1AG

iiyama TF3239AS-B1AG. Konstrukcja produktu: Płaski panel Digital Signage. Długość przekątnej ekranu: 80 cm (31.5"), Technologia wyświetlacza: LED, Rozdzielczość: 1920 x 1080 px, Jasność: 500 cd/m², Typ HD: 2.4K Ultra HD, Ekran dotykowy. Czas pracy (godziny / dni): 24/7. Zainstalowany system operacyjny: Android. Kolor produktu: Czarny

| Display | |
|---|---|
| Panel type | IPS |
| LED backlight | ✔ |
| Display diagonal * | 80 cm (31.5") |
| Display technology * | LED |
| Display resolution * | 1920 x 1080 pixels |
| Display brightness * | 500 cd/m² |
| HD type * | 2.4K Ultra HD |
| Touchscreen * | ✔ |
| Number of simultaneous touchpoints | 40 |
| Multi-touch | ✔ |
| Native aspect ratio | 16:9 |
| Response time | 8 ms |
| Contrast ratio (typical) | 1200:1 |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| Display number of colours | 16.7 million colours |
| Pixel pitch | 0.363 x 0.363 mm |
| Active display area (W x H) | 698.4 x 392.8 mm |
| Display diagonal (metric) | 80 cm |
| Horizontal scan range | 28 - 160 kHz |
| Native refresh rate | 60 Hz |
| Haze rate | 25% |
| Surface hardness | 3H |
| Glass thickness | 3 mm |

| Ports & interfaces | |
|---|---|
| HDMI ports quantity * | 2 |
| HDMI version | 2.0 |
| DVI port * | ✘ |
| DisplayPorts quantity * | 1 |

| Design | |
|---|---|
| Bezel width (top) | 2.2 cm |

| Performance | |
|---|---|
| Purpose * | Universal |
| On Screen Display (OSD) | ✔ |
| Number of OSD languages | 13 |
| On Screen Display (OSD) languages | Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Polish, Russian, Slovenian |
| Operating hours (hours/days) | 24/7 |
| HDCP | ✔ |
| International Protection (IP) code | IP54 |
| HDCP version | 2.2 |
| Mean time between failures (MTBF) | 50000 h |

| Power | |
|---|---|
| Power consumption (typical) * | 50 W |
| Power consumption (standby) * | 0.5 W |
| Power consumption (off) | 0.3 W |
| Energy efficiency class (SDR) | F |
| Energy consumption (SDR) per 1000 hours | 31 kWh |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50/60 Hz |
| Energy efficiency scale | A to G |

| Computer system | |
|---|---|
| Computer system * | ✔ |
| Built-in processor * | ✔ |
| Processor manufacturer | ARM |
| Processor architecture | ARM Cortex-A53+Cortex-A73 |
| Internal memory | 4 GB |

| Ports & interfaces | |
|---|---|
| DisplayPort version | 1.2 |
| USB port * | ✔ |
| USB ports quantity | 3 |
| USB version | 2.0 |
| USB connector type | USB Type-A, USB Type-B |
| USB 2.0 Type-B ports quantity | 1 |
| Ethernet LAN * | ✔ |
| Ethernet LAN (RJ-45) ports | 1 |
| RS-232C | ✔ |

| Audio | |
|---|---|
| Built-in speaker(s) * | ✔ |
| Number of built-in speakers | 2 |
| RMS rated power | 20 W |

| Design | |
|---|---|
| Product design * | Digital signage flat panel |
| Placement supported * | Indoor |
| Orientation | Horizontal/Vertical |
| Product colour * | Black |
| Screen shape | Flat |
| VESA mounting * | ✔ |
| Panel mounting interface | 200 x 200 mm |
| Bezel width (bottom) | 2.2 cm |
| Bezel width (side) | 2.2 cm |

| Computer system | |
|---|---|
| Internal storage capacity | 32 GB |
| Operating system installed | Android |
| Operating system version | 11 |

| Weight & dimensions | |
|---|---|
| Display width | 746.2 mm |
| Display depth | 62.4 mm |
| Display height | 440.7 mm |
| Display weight | 13.2 kg |

| Packaging data | |
|---|---|
| Package width | 840 mm |
| Package depth | 149 mm |
| Package height | 560 mm |
| Package volume | 16600 $cm^3$ |

| Packaging content | |
|---|---|
| Remote control included | ✔ |
| Batteries included | ✔ |
| Cables included | AC, DisplayPort, HDMI, USB |

| Operational conditions | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C |

| Certificates | |
|---|---|
| Certification | TCO Certified, CB, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH |



4948570123865

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-DEC-2024. Prints or copies of Information are only valid on the printed Publication date