iiyama

iiyama LH6541UHS-B1AG signage display 163,8 cm (64.5") LCD 500 cd/m² 4K Ultra HD Czarny 24/7



Marka : iiyama

Kod produktu: LH6541UHS-B1AG

Nazwa produktu : LH6541UHS-B1AG

iiyama LH6541UHS-B1AG. Długość przekątnej ekranu: 163,8 cm (64.5"), Technologia wyświetlacza: LCD, Rozdzielczość: 3840 x 2160 px, Jasność: 500 cd/m², Typ HD: 4K Ultra HD. Czas pracy (godziny / dni): 24/7. Kolor produktu: Czarny



Display	
Panel type	VA
Display diagonal *	163.8 cm (64.5")
Display technology *	LCD
Display resolution *	3840 x 2160 pixels
Display brightness *	500 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✗
Native aspect ratio	16:9
Response time	6.5 ms
Contrast ratio (typical)	5000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.372 x 0.372 mm
Active display area (W x H)	1428.5 x 803.5 mm
Display diagonal (metric)	164 cm
Colour saturation	72%
Horizontal scan range	30 - 80 kHz

Ports & interfaces	
HDMI ports quantity *	3
HDMI version	2.0
USB port *	✓
USB version	2.0
Ethernet LAN *	✓
Ethernet LAN (RJ-45) ports	1
RS-232C	✓
Remote (IR) input	1

Audio	
Built-in speaker(s) *	✓

Design	
Panel mounting interface	500 x 500 mm

Performance	
Purpose *	Universal
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	German, Dutch, English, Spanish, French, Italian, Japanese, Russian
Operating hours (hours/days)	24/7
HDCP	✓
HDCP version	2.2
Mean time between failures (MTBF)	50000 h

Power	
Power consumption (typical) *	115 W
Power consumption (standby) *	0.5 W
Power consumption (off)	0.3 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	115 kWh
AC input voltage	100-240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G

Weight & dimensions	
Display width	1456.5 mm
Display depth	69 mm
Display height	831.5 mm
Display weight	17.7 kg

Packaging data	
Package width	1640 mm
Package depth	164 mm
Package height	990 mm

Audio	
Number of built-in speakers	2
RMS rated power	10 W

Design	
Orientation	Horizontal/Vertical
Product colour *	Black
VESA mounting *	✔

Packaging data	
Package weight	25.7 kg

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C



4948570124558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-FEB-2025. Prints or copies of Information are only valid on the printed Publication date